



PLATINUM

**FREESTANDING PLATINUM
FRIDGE GLASS DOOR
600L WHITE**



- ✓ **Large 600L Capacity**
offers maximum refrigerated storage space
- ✓ **0°C to +10°C Temperature Range**
allows user to select ideal temperature
- ✓ **5 Removable Wire Shelves, 20 Variable Shelf Positions**
offers great internal storage flexibility
- ✓ **Easy Grab Handle**
- ✓ **2/1 Gastronorm Compatible**
- ✓ **4 Fitted Castors**
with two locking at front for ease of movement
- ✓ **Lockable**
- ✓ **Replaceable Door Seal**
- ✓ **Internal LED Light**
- ✓ **Automatic Defrost**
for low on-going maintenance
- ✓ **Warning Alarms**
high/low temperature and door open alarms to alert users to a problem

SKU CODE: PRODUCT CODE:

DESCRIPTION:

44441753 CRG600W

Freestanding Platinum Fridge Glass Door 600L White



FULL SPECIFICATION – CRG600W FREESTANDING PLATINUM FRIDGE GLASS DOOR 600L WHITE



Description	Freestanding
SKU Code	444441753
EAN Code	5052263017535
GDPA Code	CRG600W
Unit External Width (mm)	775
Unit External Depth (mm)	760 (includes handle depth of 40mm)
Unit External Height (mm)	1982
Packed Width (mm)	835
Packed Depth (mm)	782
Packed Height (mm)	1995
Product Weight (kg)	101
Packed Weight (kg)	125
Internal Dimensions (mm) (WxDxH)	670x582x1653
Gross Capacity (L)	600
Net Capacity (L)	584
Material - Exterior Finish	White Painted Steel
Material - Interior Finish	Plastic (HIPS/ABS Mix)
Stackable	No
Gastronorm Compatible	Yes (2/1)
Colour	White
Internal Temperature Range	0 to +10°C
Maximum Ambient Operating Temperature	Up to 38°C
Defrost Type	Automatic
Forced Air Cooling (Fan)	Yes
Door Type	Glass
Door Style	Hinged, reversible
Self Closing Door	No
Door Open Depth (mm)	1480
Replacement Door Seal	Yes
Controller type	Electronic
Open Door Sensor/Alarm	Yes
Hi/Low Temperature Alarm	Yes
External Temperature Display	Yes
Rollers/Castors	4 fitted castors (2 lockable fronts)
Number of Shelves	5
Number of Shelf Positions	20
Shelf Size (mm) (WxD)	650x530
Shelf Material	White plastic-coated aluminium
Internal LED Light	Yes
Light Activation	Red light switch on the interior ceiling
Fitted Lock	Yes
Insulation Thickness (mm)	47
Insulation Material	Pentane
Voltage Supply	220/240v
Power Rating (kW)	0.26
Supplied with Fitted UK Plug	Yes
Fitted Cable Length (m)	1.8
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
Heat Rejection (Watts)	150
Energy Consumption (Kw/h) (24hrs)	2.4